

(12) United States Patent

Ustrell I Mussons

US 9,410,297 B2 (10) Patent No.: (45) Date of Patent:

Aug. 9, 2016

(54) MECHANISM FOR REDUCING THE SPEED OF ROAD TRAFFIC AND CORRESPONDING SPEED BUMP

(71) Applicant: Raül Ustrell I Mussons, Barcelona (ES)

Inventor: Raül Ustrell I Mussons, Barcelona (ES)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/409,544

(22) PCT Filed: Jun. 18, 2013

(86) PCT No.: PCT/ES2013/070394

§ 371 (c)(1),

(2) Date: Dec. 19, 2014

(87) PCT Pub. No.: WO2013/190159

PCT Pub. Date: Dec. 27, 2013

(65)**Prior Publication Data**

US 2015/0176232 A1 Jun. 25, 2015

(30)Foreign Application Priority Data

Jun. 19, 2012 (ES) 201230958

(51) Int. Cl. (2006.01)E01F 9/047

E01C 9/00 (2006.01)

(52) U.S. Cl. CPC .. E01F 9/047 (2013.01); E01C 9/00 (2013.01)

(58) Field of Classification Search CPC E01F 9/047; E01F 13/123; E01F 13/00;

E01F 13/12; E01F 13/10; G08G 1/07; E01C

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

| 2,917,283 A * | 12/1959 | Sumners G07F 17/145 |
|---------------|---------|--------------------------------|
| 2 205 255 4 * | 1/1067 | 194/902 Russo E01F 13/105 |
| 3,293,233 A | 1/1907 | 188/32 |
| 3,325,782 A * | 6/1967 | Der E01F 13/105 |
| 1 100 069 A * | 12/1094 | 340/935 |
| 4,490,008 A | 12/1984 | Dickinson E01F 13/08 404/11 |
| 4,974,991 A * | 12/1990 | Mandavi E01F 13/105 |
| | | 404/11 |
| 5,486,065 A * | 1/1996 | James E01F 9/047 |
| | | 404/15 |

(Continued)

FOREIGN PATENT DOCUMENTS

1 048 038 U 6/2001 ES 2 296 517 A1 4/2008

(Continued)

Primary Examiner — Abigail A Risic (74) Attorney, Agent, or Firm — McGlew and Tuttle, P.C.

(57)ABSTRACT

A mechanism for reducing the speed of road traffic and corresponding speed bump. A mechanism for reducing the speed of road traffic on public thoroughfares comprising [a] a collapsible surface (1) which moves between a raised position and a lowered position, where the collapsible surface is normally in the raised position, and [b] retaining means (19) adapted to retaining the collapsible surface in the raised position. The retaining means are activated when the speed of movement of the collapsible surface is greater than a predetermined maximum speed. With this mechanism it is possible to make a speed bump for reducing the speed of road traffic comprising one or two of these mechanisms. If it comprises two mechanisms, each of them has a width of less than 1.2 m and they are spaced apart at a distance such that an automobile rides simultaneously over both mechanisms.

17 Claims, 2 Drawing Sheets

